

	TDS	2018
---	------------	-------------

**PRODUCT: SELF-ADHESIVE SEAMING TAPE
DOUBLE SIDED**

COMPOSITION: 1,8 mm thick butyl rubber compound reinforced with a polyester mesh

HANDLING: Manual application at least 5° C

STORAGE: The quality and characteristics of materials remain unaltered for a very long time. However, it is best to use the product within 12 months.

CHARACTERISTICS: When not exposed directly to weather, high ageing resistance. Excellent adhesive properties.
Solvents and bitumen free
Application for both inside and outside use
Temperature resistance, -40°C +90°C, no shrinking, drying-out or embitterment. The short-term influence of high temperatures, does not influence functional capabilities

QUALITY CHARACTERISTICS	TECHNICAL DATA	TEST METHOD
--------------------------------	-----------------------	--------------------

Weight	2640 g/m ²	
Thickness	2.10 mm	
Tensile Strength MD	140 (N/50 mm)	EN 12311-1
Tensile Strength CD	205 (N/50 mm)	EN 12311-1
Elongation at Break MD	>15%	EN 12311-1
Elongation at Break CD	>15%	EN 12311-1

The figures represent average values and are as such indicative.
The user must always test the suitability of the product for the intended use. The user bears all associated risks and liabilities.
Nimaco is not liable for any damage as a consequence of unsuitable use of the product.