

	<b>TDS</b>	<b>2018</b>
---	------------	-------------

- PRODUCT:** **SELF-ADHESIVE SEAMING TAPE  
ONE SIDED**
- COMPOSITION:** Spunbonded polypropylene 110 g/m<sup>2</sup> with 1mm thick butyl rubber compound
- HANDLING:** Manual application at least 5° C  
The product must be protected from U.V. rays
- STORAGE:** The quality and characteristics of materials remain unaltered for a very long time. However, it is best to use the product within 12 months.
- CHARACTERISTICS:** When not exposed directly to weather, high ageing resistance. Excellent adhesive properties.  
Solvents and bitumen free  
Application for both inside and outside use  
Temperature resistance, -30°C +80°C, no shrinking, drying-out or embitterment. The short-term influence of high temperatures, does not influence functional capabilities

QUALITY CHARACTERISTICS	TECHNICAL DATA	TEST METHOD
-------------------------	----------------	-------------

Weight	2055 g/m <sup>2</sup>	
Thickness	1.45 mm	
Tensile Strength	7,3 kN/m	EN ISO 10319
Elongation at Break	52%	EN ISO 10319

The figures represent average values and are as such indicative.  
The user must always test the suitability of the product for the intended use. The user bears all associated risks and liabilities.  
Nimaco is not liable for any damage as a consequence of unsuitable use of the product.